

External Sensor

RN1091 Temperature & Humidity Sensor

Product features

Temperature & Humidity Sensors provide a valuable extension to our innovative monitoring system. They interface directly to any UPDU™ or E3METER™ smart PDU through their robust digital interface. Easy tool-less rack mounting assures high accuracy Temperature & Humidity measurement in different locations of a server rack.



Swiss Made

Technical Specifications

Operating Temperature	0 - +60°C (recommended) / -40 - +85° C (maximum)
Operating Humidity	0 - 100% RH non-condensing
Accuracy	Temperature +/- 0.3°C Humidity +/- 2%, factory calibrated
Connector	RJ-12, 4p
Size of the Sensor Head	10 x 40 x 7 mm
I/F to UPDU™ or E3METER™ smart PDU	Digital (with checksum)
Cable	Flexible, available lengths: 2m (other lengths on request)
Mounting	2 integrated magnets, 3mm mounting hole
Installation	Plug and play
Warranty	2 years

Disclaimer

Copyright © 2023 Riedo Networks Ltd. All rights reserved.

RNX, E3METER and UPDU are registered trademarks of Riedo Networks.

Every effort has been made to ensure that the information in this product datasheet is accurate. Anyway, the information in this product datasheet is subject to change without notice and should not be construed as a commitment by Riedo Networks Ltd.

Riedo Networks Ltd assumes no responsibility or liability for any errors or inaccuracies that may appear in this product datasheet.